

AMENDMENTS TO THE CLAIMS

Claims 1-276. (canceled)

277. (currently amended) Medical apparatus Apparatus for placement in a patient, comprising:

implantable circuitry, having medical functionality, which is adapted to be placed in the patient;

    a lead wire; and

    an electrically-conductive hollow tube connector, which hollow tube is soldered directly to the circuitry circuitry, and which hollow tube is mechanically coupled to the lead wire so as to be electrically coupled thereto.

278. (currently amended) The apparatus according to claim 277, wherein the hollow tube connector is crimped to the lead wire, so as to be mechanically coupled thereto.

279. (currently amended) The apparatus according to claim 278, ~~wherein the connector comprises a hollow tube~~, wherein a portion of the lead wire is disposed within the hollow tube, and wherein the hollow tube is crimped to the portion of the lead wire.

280. (previously presented) The apparatus according to claim 277, wherein the lead wire comprises MP35N.

281. (previously presented) The apparatus according to claim 277, wherein the lead wire comprises platinum/iridium.

282. (previously presented) The apparatus according to claim 277, wherein the lead wire comprises 1-60% iron by weight.

283. (previously presented) The apparatus according to claim 277, wherein the lead wire comprises 1-40% iron by weight.

284. (previously presented) The apparatus according to claim 277, wherein the lead wire comprises 1-20% iron by weight.

285. (currently amended) The apparatus according to claim 316 [[277]], wherein the hollow tube connector is coated with gold prior to soldering directly to the circuitry.

286. (currently amended) The apparatus according to claim 277, wherein the hollow tube is connector has been treated with phosphoric acid prior to soldering to the circuitry.

287. (previously presented) The apparatus according to claim 277, wherein the circuitry is adapted to be implanted in the patient.

288. (previously presented) The apparatus according to claim 277, wherein the circuitry is adapted to be incorporated in a catheter.

289. (previously presented) The apparatus according to claim 277, wherein the lead wire comprises a silver core.

290. (currently amended) The apparatus according to claim 277, wherein the hollow tube connector comprises stainless steel.

291. (previously presented) The apparatus according to claim 277, wherein the circuitry comprises a sensor.

292. (previously presented) The apparatus according to claim 291, wherein the sensor comprises a pressure sensor.

293. (previously presented) The apparatus according to claim 291, wherein the sensor comprises a chemical sensor.

294. (previously presented) The apparatus according to claim 291, wherein the sensor comprises an electrode, adapted to sense electrical activity in tissue of the patient where the apparatus is placed.

295. (previously presented) The apparatus according to claim 291, wherein the sensor comprises a temperature sensor.

296. (previously presented) The apparatus according to claim 291, wherein the sensor comprises a flow sensor, adapted to sense a flow of blood in a vicinity of the apparatus.

297. (previously presented) The apparatus according to claim 277, wherein the circuitry comprises an active element.

298. (previously presented) The apparatus according to claim 297, wherein the active element comprises a stimulating electrode.

299. (previously presented) The apparatus according to claim 297, wherein the active element comprises a light source adapted to facilitate photodynamic therapy.

300. (previously presented) The apparatus according to claim 297, wherein the active element comprises an electroactive polymer.

301. (previously presented) The apparatus according to claim 297, wherein the active element comprises a mechanical actuator.

302-315. (canceled)

316. (new) The apparatus according to claim 277, wherein the hollow tube is coated prior to soldering directly to the circuitry.